PRODUCT SPECIFICATIONS FOR PANELS ISOVISTA AND ACCESSORIES

ISOVISTA® PANEL

01) SUPPLY AND / OR INSTALLATION OF PANEL ISOVISTA® with strips of the line (Premium, Uniformat, Longformat), model no. (cfr. Products list), the size of mm. a x b x s (see thicknesses depending on desired transmittance) previously cleaned from mold and / or surface efflorescence, removal and marking out of damaged or detached plaster, including securing the horizontal basic aluminium profile for the panels alignment, including sealing of the base of the profile to the wall plate using silicone, including distribution of polyurethane glue supplied in spray cans in the manner of distribution set out in the technical installation, including fixing the panels to the support (concrete wall - brick - wood - precast panels - etc.) by nr. 5/6 dowels / panel, related to diameter and length indicated in the document assembly according to the thickness of the panel selected, including also filling of the joints with MisterBrick plaster color X (see colors available) by means of special applicators pockets, with preparation and crushing of the grout before the completion of the drying. Including final brushing of the joints and the entire coated surface to complete the installation, all executed in a workmanlike.

Measure on the effective surface.

 m^2 X€ / m² =€

ISOVISTA® CORNER PANEL

02) SUPPLY AND / OR INSTALLATION OF ISOVISTA® CORNER PANEL with strips of the line (Premium, Uniformat, Longformat), model no. (cfr. Products list), the size of mm. axbxlxs (see thicknesses depending on desired transmittance) previously cleaned from mold and / or surface efflorescence, removal and marking out of damaged or detached plaster, including securing the horizontal basic aluminium profile for the panels alignment, including sealing of the base of the profile to the wall plate using silicone, including distribution of polyurethane glue supplied in spray cans in the manner of distribution set out in the technical installation, including fixing of the panels to the support (concrete wall - brick - wood - precast panels - etc.) by nr. 4 dowels / panel, according diameter and length indicated in the document assembly related to the thickness of the panel selected. Including also filling of the joints with Mister Brick plaster color X (see colors available) by means of special applicators pockets, with preparation and crushing of the grout before the completion of the drying. Including final brushing of the joints and the entire coated surface to complete the installation, all executed in a workmanlike.

Measure on the effective surface.

X€ / linear meter =€ linear meter